







of Trailer Manufacturers



Standard Specifications:

LED Lights
5K Top Wind Jacks
Barn Door Style Tailgate
Adjustable Ball Coupler
Drop Axles
16" Radial Tires
7'x12', 7'x14', 7x16' Models Available
Channel Crossbeams on 16" center
3/16 Steel Floor w/Welded Seams
Treated 2x6 Top Board



Features & Specifications

- Medium Duty, Low Profile
- Available in 7' x 12' / 7' x 14' / 7' x16'
- 24" Load Height on some models
- Tailgate Barn door style
- GVW 14,000#
- LED lights
- Goose Neck available
- 2-7000# Drop Axles standard
- Slipper Spring Suspension
- 2-5/16 Adjustable Ball Coupler
- 5K Top Wind jack
- 6" Cylinder
- Heavy Duty Hydraulic Scissor Lift
- 12V Power Up and Down Hydraulic Pump - standard equipment

- 16" Silver Mod Wheels
- 235/80R 16" Radial Tires
- 1/8" Steel Sides at 20"
- Treated 2x6 Top Board for extra height and bed protection
- 3/16 Steel Floor (welded seams)
- 6" Channel Frame and Tongue
- 3" Channel Crossbeams on 16" center
- Sealed Wiring Harness with 7 way plug
- 1/8 Steel Diamond Plate Running Boards
- 1/8" Steel Diamond Plate Fenders
- 80.5" wide Inside Bed Clearance
- Sandblasted, PRIMED, & Powdercoated
- Spare Tire Mount



